



## COIN-OPERATED DRYERS

RANGE OF SIZES • FAST, EFFECTIVE DRYING • TWO STYLE CHOICES



M330C



M50EDC

Optional stainless steel panels available.

# MILNOR COIN-OP DRYERS. CHOICES FOR ANY LAUNDRY!

## Classic-style dryers for any application

Milnor's classic-line of coin-op dryers feature unique advantages making them ideal for new store development or replacement of older, less efficient dryers. Easy-to-use controls and fast dry times make these dryers a popular choice among coin store customers.

	Capacity Lbs. (kg)	Basket diameter ins. (mm)	Basket depth ins. (mm)	Basket volume cu.ft. (L)	Drive motor HP (kW)	Door opening ins. (mm)	Exhaust conn. ins. (mm)	Approx. width ins. (mm)	Approx. depth ins. (mm)	Approx. height ins. (mm)	Approx. net weight lbs. (kg)	Electric models Oven kW	Gas model voltages
<b>M330C</b>	2x30 (2x14)	2x27.25 (2x692)	2x30 (2x762)	2x10.1 (2x286)	2x.3 (2x.22)	2x21.5 (2x546)	2x6 (2x152)	29.75 (756)	43.87 (1114)	78.25 (1988)	837 (379)	15	100-240V/ 1P/50,60C
<b>M333C</b>	2x30 (2x14)	2x27.25 (2x692)	2x30 (2x762)	2x10.1 (2x286)	2x.5 (2x.37)	2x21.5 (2x546)	8 (203)	29.75 (754)	53 (1345)	78.25 (1998)	675 (306)	15	120-240V/ 1P/50,60C
<b>M30C</b>	30 (14)	32.75 (832)	25.63 (651)	12.5 (353)	.5 (.37)	21.5 (546)	8 (203)	34.25 (870)	38 (965)	72 (1828)	534 (242)	20,24	120-480V/ 1-3P/50,60C
<b>M50C</b>	50 (23)	32.75 (832)	37.5 (953)	18.3 (518)	.75 (.56)	21.5 (546)	8 (203)	34.25 (870)	49.75 (1264)	72 (1820)	651 (295)	20,24, 30	100-480V/ 1-3P/50,60C
<b>M758C</b>	75 (34)	36.25 (920)	36 (914)	21.5 (608)	1 (.75)	31.38 (797)	8 (203)	38.25 (972)	48 (1219)	75.13 (1908)	721 (327)	30	120-480V/ 1-3P/50,60C
<b>M78C</b>	75 (34)	44.5 (1130)	24.88 (632)	22.4 (634)	1 (.75)	31.38 (797)	10 (254)	46.19 (1175)	35 (889)	84.32 (2140)	888 (403)	24,36	120-480V/ 1-3P/50,60C
<b>M444C</b>	2x45 (2x20)	2x32.75 (2x832)	2x30 (2x762)	2x14.6 (2x413)	2x.75 (2x.56)	2x27 (2x686)	2x8* (2x203)	34.31 (871)	53.31 (1350)	80.94 (2056)	905 (410)	N/A	120-240V/ 1-3P/50,60C
<b>M115C</b>	115 (52)	42 (1069)	41.25 (1048)	33.1 (937)	.75 (.56)	31.38 (797)	14 (356)	46.13 (1171)	63.56 (1614)	84 (2133)	1260 (572)	N/A	208-575V/ 3P/50,60C

\*Optional 10" exhausts.

Specifications (standard models) and appearance subject to change without notice.

## EcoDry-style dryers for best efficiency

Milnor's ED dryers deliver unmatched energy savings combined with features that provide optimal drying performance. With 100% axial airflow, heat flows in from the rear and is captured in the solid steel drum where sensors efficiently manage heat.

	Capacity Lbs. (kg)	Basket diameter ins. (mm)	Basket depth ins. (mm)	Basket volume cu.ft. (L)	Drive motor HP (kW)	Door opening ins. (mm)	Exhaust conn. ins. (mm)	Approx. width ins. (mm)	Approx. depth ins. (mm)	Approx. height ins. (mm)	Approx. net weight lbs. (kg)	Electric models Oven kW	Gas model voltages
<b>M3030EDC</b>	2x30 (2x14)	2x25.75 (2x654)	2x34 (2x864)	2x10.25 (2x290)	2x.25 (2x.19)	2x19.38 (2x492)	2x6 (2x152)	27 (686)	40.59 (1031)	72.88 (1851)	535 (243)	N/A	120-240V/ 1P/50,60C
<b>M3535EDC</b>	2x35 (2x16)	2x30 (2x762)	2x30 (2x762)	2x12.27 (2x347)	2x.25 (2x.19)	2x19.38 (2x492)	2x6 (2x152)	31.13 (791)	39.58 (1007)	80.38 (2041)	600 (272)	7.9- 13.5	120-240V/ 1P/50,60C
<b>M35EDC</b>	35 (16)	30 (762)	30 (762)	12.27 (347)	.25 (.19)	19.38 (492)	6 (152)	31.13 (791)	40.42 (1027)	67 (1701)	462 (210)	7.9- 13.5	120-240V/ 1P/50,60C
<b>M50EDC</b>	50 (23)	37 (940)	25.75 (654)	16.02 (454)	.75 (.56)	27.38 (695)	8 (203)	38.25 (972)	40.13 (1019)	70.5 (1790)	610 (277)	18.5- 22	120-240V/ 1P/50,60C
<b>M76EDC</b>	75 (34)	37 (940)	35.5 (902)	22.09 (626)	.75 (.56)	27.38 (695)	8 (203)	38.25 (972)	49.81 (1265)	70.5 (1790)	745 (338)	18.4- 20.4	120-240V/ 1P/50,60C
<b>M5050EDC</b>	2x50 (2x23)	2x32.75 (2x832)	2x32.75 (2x832)	2x16 (2x453)	2x.33 (2x.25)	2x23.75" (2x603)	2x8 (2x203)	34.25" (870)	56.38 (1432)	83.75 (2076)	900 (408)	N/A	120-240V/ 1P/60C

Specifications (standard models) and appearance subject to change without notice.



PELLERIN MILNOR CORPORATION  
 P.O. BOX 400, Kenner, LA 70063  
 504/712-7656  
 Fax: 504/468-3094  
 Literature Hotline: 800/469-8780  
 Email: milnorinfo@milnor.com  
 www.milnorcoin.com

© Pellerin Milnor Corporation. Printed in U.S.A.  
 B22SL07004/13184