



# M210, M310, M410 DRYERS

WIDE RANGE OF STANDARD FEATURES ■ TWO-WAY TILT OPTION



## The features you need.

The industrial dryers come with a variety of standard features that increase productivity and enhance ease-of-use. For example:

- Advanced microprocessor accurately controls dryer function with easy, push-button commands.
- High-powered, efficient heatsources (see below for more information).
- Reliable roller-driven basket.
- Durable stainless steel basket.
- Extra large blower motor for fast drying.
- Large-capacity, easy-to-clean front lint basket.
- Electrostatic powder-paint finish is applied inside-and-out. (Most dryers are assembled and then painted only on the outside.)
- Fire Suppression System (FSS).
- Reversing feature helps prevent wrinkling.
- Cabinet and access panels are fully insulated to reduce environmental noise and heat.
- Rotational sensor adds an extra element of safety.
- Hinged front panel for maintenance ease.

Gas models use a microprocessor-controlled, instantaneous spark ignition system coupled with twin atmospheric burners. With a large blower motor, the gas model delivers fast, efficient drying.

Steam model dryers use a steam damper system, which allows the coil to stay constantly charged, eliminating repeated expansion and contraction. When the damper is opened, the air immediately passes through the already hot coil, providing instant heat to start the drying process. When the damper is closed, ambient air is drawn directly into the basket, allowing a rapid cool down. This system eliminates troublesome steam valves.

## Advanced control for top results.

An exclusive microprocessor is the most simple and efficient control. To start the machine, the operator merely selects one of six letters (A through F) and the dryer immediately begins a preprogrammed cycle which has been pre-chosen by the laundry manager. The microprocessor is capable of retaining up to 47 preprogrammed cycles.

“Anti-wrinkle” allows the dryer to cycle in a cool down mode after the cycle has finished. With “anti-wrinkle” the dryer can be programmed to tumble without heat. This feature can automatically reduce wrinkling and significantly reduce the risk of spontaneous combustion.

## Reliable drive system.

Four 11-inch diameter wheels support the stainless steel basket. These wheels protect the drive bearing by keeping it out of the heat stream.



Pellerin Milnor Corporation  
P.O. Box 400, Kenner, LA 70063 USA  
Phone: (504) 467-9591  
Toll Free: (800) 469-8780  
www.milnorcoin.com  
milnorinfo@milnor.com

## Tilting and door options.

The industrial dryers can assist loading and unloading through one- and two-way tilting options, as well as either single front door or front- and rear-door options (pass-through). Doors can be ordered as manually-operated or automatic, air-operated. This flexibility makes the industrial dryers suitable for a variety of laundries.

## Easy to service.

All major electrical and pneumatic components are conveniently located for ease of connection and maintenance. Electrical panel doors use keyed locks for safety. Hinged front and side panels enhance serviceability.



## SPECIFICATIONS

	M210	M310	M410
Max load size - lb (kg)	200 (91)	310 (141)	410 (186)
Basket volume - cu. ft. (L)	74.5 (2,110)	106.5 (3,016)	143 (4,049)
Basket diameter - in (mm)	62.5 (1,587)	62.5 (1,587)	68.75 (1,746)
Basket depth - in (mm)	42 (1,067)	60 (1,524)	66.38 (1,686)
Blower motor Gas/Steam - HP (kW)	7.5 / 15 (5.6/11.2)	15 / 25 (11.2/18.6)	15 / 25 (11.2/18.6)
Basket drive motor - HP (kW)	3 (2.2)	5 (3.7)	7.5 (5.6)
<b>GAS MODEL</b>			
Overall width* - in (mm)	78.87 (2,003)	79.12 (2,010)	98.5 (2,502)
Overall depth* - in (mm)	58.5 (1,486)	75 (1,186)	80.25 (2,038)
Max tilting depth* - in (mm)	98.09 (2,491)	119.94 (3,046)	121.12 (3,076)
Overall height (non-tilt)** - in (mm)	113.5 (2,883)	114.25 (2,902)	123.25 (3,131)
Max. tilting height**+ - in (mm)	124.97 [Rear] (3,174)	122.43 (3,110)	138.91 (3,528)
Net weight**+ - lb (kg)	3,033 (1,376)	5,000 (2,268)	6,300 (2,858)
Airflow - cfm (cmm)	5,300 (150)	6,500 (184)	9,200 (261)
Heat input - Btu/hr (kcal/hr)	650,000 (163,810)	1,125,000 (283,495)	1,400,000 (352,794)
Gas inlet - in (mm)	1.5 F.N.P.T	(2) 1.5 M.N.P.T.	1.5 F.N.P.T
Exhaust diameter - in (mm)	20 (508)	24 (610)	28 (711)
<b>STEAM MODEL</b>			
Boiler Bhp	27	35	42
Airflow - cfm (cmm) 60 Hz	6500 (184)	8500 (241)	10,300 (292)
Airflow - cfm (cmm) 50 Hz	5417 (153)	8500 (241)	10,300 (292)

\*Non-tilt dimensions are for non-tilting models. Tilting dimensions are for two way tilt.

+ These dryers are available in many configurations. All dimensions are for reference only and are subject to change without notice. Contact the factory for certified dimensions, or dimensions for other configurations.