



V-SERIES WITH E-P PLUS® CONTROL

PROGRAMMING FLEXIBILITY • TWO CAPACITIES • RINSAVE® WATER SAVER



30022 VRJ

HIGHLY PROGRAMMABLE CONTROL FOR EASE OF USE AND FLEXIBILITY



This comprehensive control can hold 30 wash formulas (including 10 pre-programmed for any of the eight industries), which allows the operator advanced flexibility. The E-P Plus owner/operator may manually create or modify

formulas, for accurate and proper washing. The E-P Plus control also features universal temperature control, programmable cooldown, programmable bath soak, and overnight soak. The two-line display notifies the operator of key benchmarks (wash step, time remaining, etc.), which increases productivity and reduces downtime.



SUPERIOR CYLINDER DESIGN

Milnor's superior cylinder design and tall, lifting ribs yield greater wash/rinse quality.

RINSAVE® WATER SAVER FEATURE



The innovative RinSave® Water Saver feature allows a precise G-force to "sling" the wash liquor (including water, chemistry, and soil) out of the goods after a wash step – saving up to 2 rinses per load and fill/rinse time.



Scan to read more about this time, water, and energy saving feature – only available from Milnor!

DEPENDABILITY IN DESIGN



Narrow Footprint: Fits through a 3'-0" doorway



Continuously welded frame for structural integrity



NEMA Premium® efficient inverter-driven motor



Safe chemical injection

SPECIFICATIONS	30015 VRJ	30022 VRJ
Capacity*-lb. (kg)	40 (18)	60 (27)
Cylinder diameter-in. (mm)	30 (762)	30 (762)
Cylinder depth-in. (mm)	15 (381)	22 (559)
Door Opening-in. (mm)	15.5 (394)	15.5 (394)
Cylinder volume-cu. Ft. (L)	6.14 (174)	9 (255)
Overall width-in. (mm)	34.5 (876)	34.5 (876)
Overall depth-in. (mm)	48.61 (1234)	55.76 (1412)
Overall height-in. (mm)	57.29 (1455)	55.56 (1466)
Motor-HP (kW)	5 (3.72)	5 (3.72)
Wash Speeds-RPM	38-43	38-43
Distribution Speed-RPM	65	65
Extraction Speeds-RPM	542-685	542-685
Max Extract Speed-RPM	685	685
Extraction G-Force	200	200
Inlet valve-in. (mm)	0.75 (19)	0.75 (19)
Drain valve-in. (mm)	3 (76)	3 (76)
Approx net weight-lb. (kg)	1,078 (489)	1,112 (504)

Specifications and appearance subject to change without notification. Contact the factory for acoustics data. *Depending on density and soil content of goods.

Printed in the U.S.A.
© Pellerin Milnor Corporation
Brochure B22SLI3002/15484



Pellerin Milnor Corporation
P.O. Box 400, Kenner, LA, 70063-0400 USA
Phone: 504.712.7656 • 800.469.8780
Fax: 504.468.3094
Email: milnorinfo@milnor.com
www.milnor.com