Published Manual Number/ECN: H000000038/2003332A

- Publishing System: TPAS
- Access date: 08/11/03
- Document ECN's: Latest Available

Kit Instruction— KWDSP00100



Please Read

About the Manual Identifying Information on the Cover

The front cover displays pertinent identifying information for this manual. Most important, are the published manual number (part number) /ECN (date code). Generally, when a replacement manual is furnished, it will have the same published manual number, but the latest available ECN. This provides the user with the latest information applicable to his machine. Similarly all documents comprising the manual will be the latest available as of the date the manual was printed, even though older ECN dates for those documents may be listed in the table of contents.

When communicating with the Milnor factory regarding this manual, please also provide the other identifying information shown on the cover, including the publishing system, access date, and whether the document ECN's are the latest available or exact.

References to Yellow Troubleshooting Pages

This manual may contain references to "yellow pages." Although the pages containing troubleshooting procedures are no longer printed on yellow paper, troubleshooting instructions, if any, will be contained in the easily located "Troubleshooting" chapter or section. See the table of contents.

Trademarks of Pellerin Milnor Corporation

The following, some of which may be used in this manual, are trademarks of Pellerin Milnor Corporation:

Ampsaver®	Dye-Extractor [®]	Gear Guardian®	Milnet [®]	Staph-Guard [®]
Autolint [®]	Dyextractor®	Hands-Off [®]	Milnor [®]	System 4 [®]
Auto-Purge [®]	E-P Express [®]	Hydro-Cushion [®]	Miltrac	System 7 [®]
Autovac	E-P OneTouch [®]	Mildata [®]	Miltron	Totaltrol [®]
$\operatorname{CBW}^{\mathbb{R}}$	E-P Plus [®]			

Comments and Suggestions

Help us to improve this manual by sending your comments to:

Pellerin Milnor Corporation Attn: Technical Publications P. O. Box 400 Kenner, LA 70063-0400

Fax: (504) 469-1849

INSTRUCTIONS FOR KIT KWDSP00100 DRYER DISCHARGE DOOR SEAL PROTECT STRIPS

The purpose of this kit is to protect the felt seal on the discharge door with a rubber flap seal. The rubber strip is installed at the bottom half of the dryer discharge door below the door ring weldment. The kit consists of a rubber flap, three brackets that hold the rubber strip to the discharge door and the associated mounting hardware.

The rear door must be disassembled and the insulation removed to drill and install this kit. Some of the weld on the door ring weldment may need grinding for the mounting strips to be installed properly. Please see drawings A75SD002B and 07-50209 for proper installation and mounting locations for the applicable parts.



