



V-SERIES WITH E-P PLUS® CONTROL

PROGRAMMING FLEXIBILITY • TWO CAPACITIES • RINSAVE® WATER SAVER



30022 VRJ

HIGHLY PROGRAMMABLE CONTROL FOR EASE OF USE AND FLEXIBILITY



This comprehensive control can hold 30 wash formulas (including 10 pre-programmed for any of the eight industries), which allows the operator advanced flexibility. The E-P Plus owner/operator may manually create or modify formulas, for accurate and proper washing.

The E-P Plus control also features universal temperature control, programmable cooldown, programmable bath soak, and overnight soak. The two-line display notifies the operator of key benchmarks (wash step, time remaining, etc.), which increases productivity and reduces downtime.

RINSAVE® WATER SAVER FEATURE



The innovative RinSave® Water Saver feature allows a precise G-force to "sling" the wash liquor (including water, chemistry, and soil) out of the goods after a wash step — saving up to 2 rinses per load and fill/rinse time and saving thousands of gallons of water every year.

SUPERIOR CYLINDER DESIGN



Milnor's tall rib construction and precise cylinder speeds combine to provide excellent MAF — Mechanical Action Factor — delivering greater wash/rinse quality and reducing time-consuming and costly rewashes.

DEPENDABILITY IN DESIGN



Narrow Footprint: Fits through a 3'-0" doorway



Continuously welded frame for structural integrity



NEMA Premium® efficient inverter-driven motor



Safe chemical injection

SPECIFICATIONS	30015 VRJ	30022 VRJ
Capacity*-lb. (kg)	40 (18)	60 (27)
Cylinder Diameter-in. (mm)	30 (762)	30 (762)
Cylinder Depth-in. (mm)	15 (381)	22 (559)
Door Opening-in. (mm)	15.5 (394)	15.5 (394)
Cylinder Volume-cu. Ft. (L)	6.14 (174)	9 (255)
Overall Width-in. (mm)	34.5 (876)	34.5 (876)
Overall Depth-in. (mm)	48.61 (1234)	55.69 (1415)
Overall Height-in. (mm)	57.29 (1455)	57.56 (1462)
Motor-HP (kW)	5 (3.72)	5 (3.72)
Wash Speeds-RPM	38-43	38-43
Distribution Speed-RPM	65	65
Extraction Speeds-RPM	542-685	542-685
Max Extract Speed-RPM	685	685
Extraction G-Force	200	200
Inlet Valve-in. (mm)	0.75 (19)	0.75 (19)
Drain Valve-in. (mm)	3 (76)	3 (76)
Approx Gross Weight-lb (kg)	1082 (491)	1138 (516)

Specifications and appearance subject to change without notification. Contact the factory for acoustics data. *Depending on density and soil content of goods.

Printed in the U.S.A.
© Pellerin Milnor Corporation
Brochure B22SLI3002/21125



Pellerin Milnor Corporation
P.O. Box 400, Kenner, LA, 70063-0400 USA
Phone: 504.712.7656 • 800.469.8780
Email: milnorinfo@milnor.com
www.milnor.com